

The foundamental parameters of X-ray telescopes



C. Vignali, M. Dadina



..since the birth of X-ray Astronomy in 1962, improvements were carried out in terms of sensitivity, angular resolution, energy resolution and energy bandpass



The Golden age of X-ray Astronomy





Chandra





Suzaku



Sensitivity:





Angular resolution (PSF FWHM, on-axis vs. off-axis, ...)





Point Spread Function (PSF) – describes the response of an imaging system to a point source or point object.

HEW (PSF), FWHM (PSF) = angular resolution

PSF = function of (x,y) or (r, ϑ) .

Chandra

High Resolution Mirror Assembly (HRMA): On-axis PSF





High Resolution Mirror Assembly (HRMA): Off-axis PSF





CDF-N 2Ms exposure

Resulting image on the focal plane of *Chandra*-ACIS



XMM-Newton: the EPIC on-axis PSF



spider-like pattern due to the support of the Wolter I mirrors

Mirror module	2	3	4
Instr. chain ^a	\mathbf{pn}	MOS-1+RGS-1	MOS-2+RGS-2
	orbit/ground	orbit/ground	orbit/ground
FWHM ["]	$< 12.5^{b}/6.6$	4.3/6.0	4.4/4.5
HEW["]	15.2/15.1	13.8/13.6	13.0/12.8

PSF FWHM higher than in *Chandra* but much larger effective area Background (and confusion limit) can be an issue

110 arcsec

XMM-Newton: the EPIC on-axis PSF



XMM-Newton: the EPIC off-axis PSF



Chandra and XMM-Newton (telescopes and CCD detectors)

Chandra = angular resolution



Only four, robust shells High-quality of shell production to allow <arcsec on-axis angular resolution (the best so far in X-rays)

To focus X-rays, angles < critical angle for total reflection are needed



High Resolution Mirror Assembly (HRMA)





Chandra focal-plane detectors: CCDs



XMM-Newton = large effective area

3 modules, 58 shells





XMM-Newton: all instruments at work simultaneously





Effective area (and its dependencies)

Mirrors and Effective Area



- Effective area it is the area "encoded" in the ARF [cm²]
- **Geometric area** "cross-section" of the telescope
- **Reflectivity** fraction of photons reflected by the mirros (function of energy)
- **Vignetting** quantifies the fraction of "lost" photons (function of the offaxis angle from the optical axis, 9, and the energy of the incoming photon)
- **Quantum Efficiency** fraction of incident photons on the detector actually registered by the detector. In the case of CCD, QE=f(energy, position on the detector)

Chandra High Resolution Mirror Assembly (HRMA): Effective Area





Chandra: Effective area



Chandra: vignetting

Ratio of the off-axis vs. on-axis counts at different off-axis angles



Hard X-ray photons are more difficult to focus → Vignetting

Chandra: Quantum efficiency



XMM-Newton: mirror effective (geometric) area





XMM-Newton: effective area



Energy [keV]

XMM-Newton: vignetting



XMM-Newton: quantum efficiency



Strong decrease in the QE above 10 keV, where also the effective area due to the mirrors has a significant decrease

XMM-Newton: effective area dependence on the filter choice



To avoid contamination from bright, soft objects (e.g., stars), a medium/thick filter is adopted

You will account for all this information creating a file named arf (ancillary response file)

Chandra

XMM-Newton



Spectral (energy) resolution

esolution t 6 keV $E^{-1/2}$ (E in keV)

0

2000

Typical CCD resolution 100-150 eV at 6 keV

 $\Delta E(FWHM)/E \propto E^{-1/2}$ (E in keV)

XMM-Newton: energy resolution



Chandra: energy resolution

6000

8000

10000

4000

Energy (eV)

You will account for all this information creating a file named rmf (redistribution matrix file)



INTEGRAL, Swift BAT NuSTAR











1 Ms Sensitivity

3.2 x 10⁻¹⁵ erg/cm²/s (6 – 10 keV) 1.4 x 10⁻¹⁴ (10 – 30 keV)

Timing

relative 100 microsec absolute 3 msec

Imaging

HPD	58"
FWHM	16"
Localization	2" (1-sigma)

Spectral response

energy range 3-79 keVthreshold2.0 keV $\Delta E @ 6 \text{ keV}$ 0.4 keV FWHM $\Delta E @ 60 \text{ keV}$ 1.0 keV FWHM

Field of View

FWZI	12.5' x 12.5'
FWHI	10' @ 10 keV
	8' @ 40 keV
	6' @ 68 keV

Target of Opportunity

response <24 hr (reqmt) typical 6-8 hours 80% sky accessibility

Focal Plane Detector

Focal Plane Parameter	Value
Detector Anode	32 pixel x 32 pixel
Pixel Size	0.6 mm/12.3"
Focal Plane Size	12' x 12'
Energy threshold	2 keV
Time resolution	2ms
Dead time fraction (at threshold)	5%
Max processing rate	400 events s ⁻¹ module ⁻¹
Max. flux meas. rate	10 ⁴ counts s ⁻¹

Number of FPDs: 2 Material: CdZnTe 1 FPD ⇒ 4 detectors (2x2 array) Detector area =2 x 2 cm Detector thickness = 2 mm



Focal Plane Detector

⁵⁷Co spectrum of one CZT pixel (gamma-ray lines at 6.40, 7.06, 14.4, 122 and 136 keV).

The 146 keV peak is produced by the test pulser.



Operating settings: Temperature = 278 K High voltage= -450 V Acquisition time = one day Energy resolution: @ 14.4 keV = 0.5 keV @ 122 keV = 0.9 keV



Cassiopeia A



Red: NuSTAR Fe Blue: NuSTAR 10-25 keV Green: Chandra 4-6 keV